

## Series DEG/MC

### Oils and grease separation unit for kitchens.

#### Technical specifications

Supply of a prefabricated monobloc vertical axis cylinder separation unit type EMS WATER TECHNOLOGY series DEG/MC, made of highly resistant reinforced concrete, dimensioned according to the DIN 4040 and UNI EN 1825 regulations, complete with deflectors, oils and grease storage zone and manhole inspections.



In compliance with the DIN 4040 regulations. Discharge in public sewer. Leg Decree n. 152 dated 03/04/06

| MODEL      | NUMBER CLIENTS A DAY | DIAMETER<br>cm | HEIGHT<br>cm | WEIGHT<br>q.l.s |
|------------|----------------------|----------------|--------------|-----------------|
| DEG/MC 30  | Fino a 30            | 130            | 220          | 12              |
| DEG/MC 70  | da 31 a 70           | 151            | 230          | 31              |
| DEG/MC 120 | da 71 a 120          | 192            | 250          | 35              |
| DEG/MC 200 | da 121 a 200         | 192            | 306          | 42              |
| DEG/MC 300 | da 201 a 300         | 248            | 310          | 70              |
| DEG/MC 400 | da 301 a 400         | 248            | 365          | 77              |
| DEG/MC 500 | da 401 a 500         | 248            | 400          | 79              |
| DEG/MC 600 | da 501 a 600         | 248            | 430          | 85              |

The values stated are just for information. EMS WATER TECHNOLOGY retains the right to change them at any time.